

characteristics ESD Nexxit 3 with glides and footring

Article: 9031E Supertec

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	570-820
		B:	460
		T:	400-460
Packing data	Weight	kg	20,5
	Volume	m ³	0,175



Base equipment

Benefit

Conductivity	The metal components have a conductive coating The high-comfort upholstery is also conductive Typical discharge resistance of 10 ⁶ Ohm Conductive castors.	Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1 100% ESD protection.
Backrest	Ergonomically shaped backrest with horizontal stitching, tapers upwards. Backrest height adjustment by 60 mm	Relieves the strain on the spine and muscles. Healthy sitting posture due to the wide support for the back around the lumbar vertebrae. Pleasant microclimate on the back and optimum freedom of movement for the arms. Ensures that people are ideally supported - especially around the lumbar vertebrae - no matter their size.
Seating surface	Ergonomically shaped seating surface with chamfer integrated into the edge of the seat.	Automatically requires the sitting posture to be correct. The chamfers prevent blood congestion in the thighs.
Upholstered Seat	Supertec ESD (innovation): Soft and comfortable, breathable and very resistant. Cut-proof, non-slip and easy to clean. Schnitffest, rutschfest und reinigungsfreundlich. Fire protection according to EN 1021 Part 1 + 2 Colour: Black.	This brand-new upholstery material is for comfortable and robust working chairs in industrial environments. Excellent seating comfort due to breathable inner layer of fabric. Micro-plating protects surface damage from sharp-edged instruments.
Functional handles	Stable and robust functional handles on the backrest. Available in the colour black (3218).	Maximum mobility and simple handling of the chair.
Base	5 star base made from steel shape tube, powder-coated. Flat design.	Very high stability, longevity. Flat design prevents stumbling hazard.
Foot ring	Chromed height-adjustable foot ring.	Provides support thanks to the wide step area and the height can be adjusted simply and quickly.
Glides	Large and abrasion-resistant plastic floor gliders.	Excellent stability
Material	The material used is recyclable.	Environmentally friendly.

characteristics ESD Nexxit 3 with glides and footring

Article: 9031E Supertec

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	570-820
		B:	460
		T:	400-460
Packing data	Weight	kg	20,5
	Volume	m ³	0,175



Technology Synchronous technology with automatic weight adjustment, incl. manual precision adjustment and angle limitation in three settings.

Ideal support which makes it possible to switch between various sitting postures at the same time. This enables dynamic sitting, relaxes the muscles, relieves the strain on the discs, improves blood flow and significantly increases concentration and performance. The backrest pressure is adapted automatically. Additional precision adjustment is possible. Several users can use the chair in alternation without having to constantly reset the weight adjustment.

Seat inclination adjustment by 6°

Many tasks are performed in a posture which is slightly raised and angled forwards. A correspondingly inclined seating surface ensures a seating angle of at least 90° while contact with the backrest is maintained.

Seat depth adjustment by 60 mm

Adapts the depth of the seat to the body size and therefore provides an ideal surface for the thighs to rest on. Contact with the backrest and therefore its support is always retained.

Standards Rapid adjustment
 DIN 68 877
 GS certificate for "tested safety"
 DIN EN ISO 9001 quality management
 DIN EN ISO 14001 environmental management
 EMAS tested environmental management
 OHSAS 18001 occupational health and safety management
 EcoVadis CSR rating 2015 Gold.

All functions can be operated conveniently and simply while seated using the operating lever. Verified by certificates from independent testing institutes, quality, environmental friendliness and procurement security.

Guarantee 10-year long-term-guarantee - 3 years of which full guarantee.

Quality assured and cost effective. Exchange of parts, free of charge, within the guaranteed period.

characteristics ESD Nexxit 3 with glides and footring

Article: 9031E Supertec

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	570-820
		B:	460
		T:	400-460
Packing data	Weight	kg	20,5
	Volume	m ³	0,175



Options		Benefit
Base	Aluminium base polished.	High quality. Attractive design.
Armrests	Multifunctional armrest Height-adjustable (100 mm), width-adjustable (continuously by increments of 25 mm), depth-adjustable (50 mm), pivotable (30°), soft armrest pads.	The armrests relieve the neck muscles. The adjustment options guarantee the ideal position for all users.