

Direct Plug-In USB Headsets



Order Code
JPL-502S-USB

Order Code
JPL-501S-USB

TECHNICAL DATA

Microphone:

Directional: Bi-directional
 Impedance: Max. 2.2K Ω 1KH(RL=2.2K Ω)
 Sensitivity: -43 \pm 3dB RL=2.2K Ω Vs=2.0V (DC)
 Frequency Range: 100-10000Hz
 Operating Temp: -25 $^{\circ}$ C~+70 $^{\circ}$ C
 Storage Temp: -40 $^{\circ}$ C~+80 $^{\circ}$ C

Speaker:

Impedance: 150 Ω \pm 15% at 0.1 V1000Hz
 Sound pressure: 129dB \pm 3dB at 1000HZ
 Frequency range: FO ~20KHZ(\pm 10dB)
 FO: 210Hz \pm 20%
 Operating Temp: -25 $^{\circ}$ C 50 $^{\circ}$ C
 Storage Temp: -25 $^{\circ}$ C 60 $^{\circ}$ C



USB-A



CLOTHING CLIP



JPL-501S / 502S

Improved sound quality and a flexible microphone boom arm with **Surround Shield™** noise cancellation.

Overview

Features	Single or dual ear Left / right ear side compatible Surround Shield™ noise cancelling microphone Clear, crisp sound 'Put and stay' ratchet microphone boom arm Overhead, sure-fit fully adjustable headband Fitted with 50mm leatherette ear cushions for maximum all day comfort
What's included	Clothing clip, Quick Start Guide and In-Line Control with Volume & Mute
Headset Weight	Mid-weight Headset, ~ 70g / ~106g
Connection	USB-A
Compatibility	Direct Plug-in
Certifications	CE, RoHS, REACH
Warranty	2 Years repair or replacement warranty
MOQ	Master Shipping Carton: 40
EAN:	JPL-501S-USB: 5060126958055, JPL-502S-USB: 5060126958079
SKU:	JPL-501S-USB: 575-329-0013, JPL-502S-USB: 575-329-002

